



# SJS1200

SJS + Smart Jump Start Charger

12,000mAh (44.4Whr)  
LITHIUM POLYMER  
BATTERY CELL



Max.Cell Power  
**1200Amp**  
Max.Peak Clamp Power  
**500Amp**  
Max.Start Clamp Power  
**200Amp**

**Will jump start MOST vehicles:**

Up to 2.8L(2800cc) DIESEL

Up to 6.0L(6000cc) PETROL



## Zip carry case contents:

- 12V 12,000mAh (44.4Whr) Lipo Power Pack
- Insulated Jump Start Safe Jumper Leads
- 240V AC/15V DC 1A Wall Charger
- 12V DC/15V DC 1A car charger
- USB 5V 2 in 1 Adaptor cable
- User manual and Instruction cards

## NEW Features:

- Jumper leads with advanced **JUMP START SAFE™**  
Technology fully automatic with  
**VOLTAGE DETECTION SAFETY PROTECTION.**
- LCD display screen to show BATTERY CAPACITY
- Ultra compact and lightweight design

## Technical data:

- **Size:** L: 165mm W: 75mm H: 35mm (Power Pack only)
- **Weight:** 415g (Power Pack only)
- **Battery:** 12V Lithium Polymer 12,000mAh (45 Whr) 3S
- **Max. Current:** 1200A Absolute . 500A PEAK at clamps 200A START at clamps
- **Output:** Jump Port 2V DC
- Device powering 12V DC up to 180watts. Use SSCFCL156 Adapto (Sold seperately)
- **Digital Charging Ports:** USB x3 / 5V 2.1A x2 / 5V 1A x1
- **Battery Chargers:** AS approved 240V AC/15V 1A DC. 12V DC/15V DC 1A Car Charger
- **Recharge Time:** 4 hrs from flat with 240V charger, 8hrs with Car charger
- **Charge Indictator:** Backlit LCD Diisplay screen
- **Self Discharge Rate:** approx. 0.2V per month depending on ambient storage temperature
- **Protection & Safety:** Reverse Current , Reverse Polarity , Short Circuit , Overtemp, Overcranking, Surge, Voltage Differential , Overload Reset, Over Charge, Over Discharge
- **LED Flashlight:** 3 Mode , Full , S.O.S , Emergency Flash
- **Operating Temperature Range:** -20 deg C to 60 deg C

UPDATED ON 23/01/2018

