

12V AC/DC 3U LED GLOBES



Product Features:

- Input voltage: 12V AC/DC 50/60Hz
- Nominal current: 1A
- Material: PBT & glass
- Wattage: 9W
- LED chips: 48pcs 2835 LED
- Ambient Temp: -15 to 50°C (The life of the lamp will gradually reduce if used outside these temperature parameters)
- Not suitable for dimming
- Recommended iron core(only) transformer & Constant Voltage LED driver



| Part No. | Description | Lamp holder | Kelvin (K) | Lumens (LM) | Watt (W) | Length (mm) | Diam (mm) | Weight (kg) | Box (cm) | Carton QTY |
|----------|---------------------------|----------------|---------------|----------------|-------------|----------------|--------------|----------------|-------------|---------------|
| 3U001 | GLOBE LED 12V AC/DC ES 3U | E27 | 3000 | 720 | 9 | 140 | Ø41 | 0.1 | 16x4.5x4.5 | 1/100 |
| 3U002 | GLOBE LED 12V AC/DC ES 3U | E27 | 4000 | 760 | 9 | 140 | Ø41 | 0.1 | 16x4.5x4.5 | 1/100 |
| 3U003 | GLOBE LED 12V AC/DC ES 3U | E27 | 6500 | 780 | 9 | 140 | Ø41 | 0.1 | 16x4.5x4.5 | 1/100 |

Recommended Transformer or Driver:

| S.N. | Brand | Part No. | Туре | QTY of Lamps | |
|------|----------|----------------|-----------------------|--------------|--|
| 1 | CLA | CLA113011 | LED Driver | 1-2 pcs | |
| 2 | CLA | CLA115011 | LED Driver | 1-4 pcs | |
| 3 | CLA | CLA1110011 | LED Driver | 1-7 pcs | |
| 4 | CLA | CLA1115011 | LED Driver | 1-12 pcs | |
| 5 | CLA | CLA1120011 | LED Driver | 2-17 pcs | |
| 6 | AQUATRAN | AQ012-050/1415 | Iron Core Transformer | 1-4 pcs | |

When calculating quantity of lamps to be used per driver or transformer:

Minimum Load: 10% of rated power; Maximum Load: 80% of rated power.