

## SURFACE MOUNTED LED WALL LIGHTS

• Input voltage: 240V AC

• Wattage: 2.4W

• 12pcs SMD5050 LED chips

• Die cast aluminium matt black or silver

Internal LED driver included

Not suitable for dimming

Mounting U bracket: 113x30mm














▲ CLA4136

**▲ CLA4186** 



CODE	DESCRIPTION	TECHNICAL DATA				DIMENSIONS			
		KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	WIDTH (mm)	DEPTH (mm)	CARTON QTY	
CLA4136W	LED S/M WALL LIGHT MATT BLK SQ 3000K	3000	170	2.4	75	120x120	60	1/20	
CLA4136C	LED S/M WALL LIGHT MATT BLK SQ 5000K	5000	170	2.4	75	120x120	60	1/20	
CLA4186W	LED S/M WALL LIGHT SIL SQ 3000K	3000	170	2.4	75	120x120	60	1/20	
CLA4186C	LED S/M WALL LIGHT SIL SQ 5000K	5000	170	2.4	75	120x120	60	1/20	

## SURFACE MOUNTED LED WALL LIGHTS

• Input voltage: 240V AC

• Wattage: 1.8W

• 9pcs SMD5050 LED chips

Die cast aluminium matt black or silver

Internal LED driver included

Not suitable for dimming


Mounting u bracket: 225x30mm















▲ CLA4536

**▲ CLA4586** 

CODE	DESCRIPTION	TECHNICAL DATA				DIMENSIONS		
		KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	HEIGHT (mm)	WIDTH (mm)	CARTON QTY
CLA4536W	LED S/M WALL LIGHT MATT BLK RECT 3000K	3000	130	1.8	75	210	82	1/20
CLA4536C	LED S/M WALL LIGHT MATT BLK RECT 5000K	5000	130	1.8	75	210	82	1/20
CLA4586W	LED S/M WALL LIGHT SIL RECT 3000K	3000	130	1.8	75	210	82	1/20
CLA4586C	LED S/M WALL LIGHT SIL RECT 5000K	5000	130	1.8	75	210	82	1/20

UPDATED ON 27.02.2017

**Tel:** +64 9 427 6133 | **Fax:** +64 9 427 6134

**Email:** sales@clalighting.co.nz | **Website:** www.clalighting.co.nz

