





# SEC SERIES **IP65**

## Surface Mounted LED *Tri-CCT* Double Adjustable Wall / Pillar Lights with / without Sensor

- Input voltage: 240V AC 50/60Hz
- Inbuilt Constant Current LED driver
- Adjustable: 180° (90° up/down and left/right)
- Housing: powder coated aluminium for SEC08-09; anodized aluminium for SEC10
- Mounting bracket: aluminium
- Diffuser: clear glass with honeycomb filter
- Tri-CCT (3000K/ 4000K/ 5500K) in one fitting
- CCT inbuilt switch under back plate
- LED chips: 1616 LEDs
- CRI: ≥80
- Power factor: ≥0.9
- Ambient temperature: -10 to 40°C
- Not suitable for dimming
- Suitable for 2 way switching

### Sensor Technical Spec:

- Sensor type: PIR sensor
- Installation height: recommended 2-2.5m
- Detection angle: 120°
- Detection area: max.10m
- Detection range (ØxH): max.10m when installed 2-2.5m
- Time delay: 8±5 sec to 12±2 min (adjustable)
- Manual override: yes



SEC08



SEC08S



SEC09




SEC09S



SEC10



SEC10S



Part No.	Description	Colour	Lumens (LM)			Watt	Box Weight (kg)	Box Size (cm)	Carton QTY
			3000K	4000K	5500K				
SEC08	D/ADJ LED MATTE WH No sensor	White	2X760	2X800	2X850	2X8W	1.2	16x13x13	1/10
SEC09	D/ADJ LED MATTE BLK No sensor	Black	2X760	2X800	2X850	2X8W	1.2	16x13x13	1/10
SEC10	D/ADJ LED TITANIUM No sensor	Titanium	2X760	2X800	2X850	2X8W	1.2	16x13x13	1/10
SEC08S	D/ADJ LED MATTE WH + sensor	White	2X760	2X800	2X850	2X8W	1.2	16x13x13	1/10
SEC09S	D/ADJ LED MATTE BLK + sensor	Black	2X760	2X800	2X850	2X8W	1.2	16x13x13	1/10
SEC10S	D/ADJ LED TITANIUM + sensor	Titanium	2X760	2X800	2X850	2X8W	1.2	16x13x13	1/10