




MR16 EXTERIOR 12V INGROUND UP LIGHTERS (small faceplates)



PRODUCT FEATURES

- Input voltage range: 12-25V DC / AC
- External Control Gear Required
- Faceplate: 316 Stainless steel
- Housing: 316 Stainless steel
- Lamp holder: MR16 (Max 20W halogen globe)
- Globe not included
- Plastic sleeve included (must be used when installing in concrete)
- Fitting slides into sleeve and remains unattached
- Cable included (L950mm)
- 4mm tempered glass, max load capacity 100kg



IGM1SS



IGM2SS



IGM3SS



IGM4SS

| PART NO. | DESCRIPTION | COLOUR | WEIGHT (KG) | BOX (CM) | CARTON QTY |
|----------|--|------------------------------------|-------------|--------------|------------|
| IGM1SS | INGROUND / WALL 1 WAY MR16 12V SS316 RND | 316 Stainless steel clear anodized | 0.4 | 13 x 10 x 10 | 1/20 |
| IGM2SS | INGROUND / WALL 2 WAY MR16 12V SS316 RND | 316 Stainless steel clear anodized | 0.4 | 13 x 10 x 10 | 1/20 |
| IGM3SS | INGROUND / WALL 3 WAY MR16 12V SS316 RND | 316 Stainless steel clear anodized | 0.4 | 13 x 10 x 10 | 1/20 |
| IGM4SS | INGROUND / WALL 4 WAY MR16 12V SS316 RND | 316 Stainless steel clear anodized | 0.4 | 13 x 10 x 10 | 1/20 |