



COMET SERIES

LED Tri-CCT **DIMMABLE** Centre Tilt Recessed downlights

3000K 4200K 6000K

3 CCT IN ONE FITTING



General Lighting



COMET01



COMET03



COMET02



COMET04


Product Features:

- Input voltage range: 185-265V AC 50/60Hz
- Constant current LED driver included
- Material: aluminium body & PMMA lens
- Heatsink: aluminium
- Centre tilt: 25°
- LED chips: 1pc COB LED
- Power factor: ≥0.9
- Ambient temp: -20 to 40°C
- Flex & plug: COMET01&03: 1640mm; COMET02&04: 1460mm
- Suitable for 2-way switching
- Suitable for dimming
- Suitable for 3 wire motion & microwave sensors

| | | | | |
|-------------------|----------------|------------|-----------------------------|------------------------|
| 30,000hr Lifetime | 50° Beam Angle | IP20 Rated | 3 YEAR Replacement Warranty | IC-F ABUTTED & COVERED |
|-------------------|----------------|------------|-----------------------------|------------------------|




TRI-CCT SWITCH ON THE FITTING




Tested & Recommended Dimmers:

| Brand | Part No. | PCS per Dimmer |
|---------|--|----------------|
| CLA | LYNX & VELA | 1-8pcs |
| Diginet | MEDM & MMDM/RT | |
| CLIPSAL | 32ELEDM-WE, 32E450TM, 32E450LM, 32E450UDM & 31E2PUDM | |
| HPM | CAT250L, CAT250T & CAT400T | |



COMET01 & 03



COMET02 & 04

| Part No. | Description | Kelvin | Lumens | Watt | CRI | Diam | Depth | Cut Out | Carton QTY |
|----------|---|-------------------|----------------|------|-----|--------|-------|----------|------------|
| COMET01 | D/L LED DIMM C/TILT MATT BL RND LOW GLARE Tri | 3000/4200/6000K | 750/850/800lm | 10W | 80 | Ø100mm | 107mm | Ø90mm | 1/24 |
| COMET02 | D/L LED DIMM C/TILT MATT Brushed Nickel Tri | 3000/ 4200/ 6000K | 800/900/ 850lm | 10W | 80 | Ø100mm | 85mm | Ø70-90mm | 1/24 |
| COMET03 | D/L LED DIMM C/TILT MATT WH RND LOW GLARE Tri | 3000/ 4200/ 6000K | 750/850/ 800lm | 10W | 80 | Ø100mm | 107mm | Ø90mm | 1/24 |
| COMET04 | D/L LED DIMM C/TILT MATT WH RND Tri | 3000/ 4200/ 6000K | 800/900/ 850lm | 10W | 80 | Ø100mm | 85mm | Ø70-90mm | 1/24 |