

sales@clalighting.co.nz Tel: +64 9 427 6133 | Fax: +64 9 427 6134



SHOPTRI LED Tri-CCT Dimmable Shop Lighter



Product Features:

- Input voltage: 200-240V AC 50/60Hz
- External constant current dimmable driver included
- Housing: white powder coated aluminium
- Textured clear glass diffuser
- Mounting plate & heatsink: aluminium
- Surface mounted or recessed
- Adjustable: 90°
- Tri-CCT (3000K / 4000K / 5700K) switch on DC cable
- LED chips: SMD2835
- Power factor: 0.95
- CRI: ≥80
- Flex & plug: 1200mm
- Mounting bracket: L 222mm x W 28.2mm
- Suitable for dimming
- Suitable for 2 way switching
- Suitable for use with PIR or Microwave sensors
- Ambient temp: -20 to 40°C



Tested & Recommended Dimmers: (1-6pcs/dimmer)

(1) CLIPSAL: 32ELEDM, 32E450UDM, 31E2PUDM;

- (2) HPM: Cat250, Cat250T, Cat400T
- (3) CLA: LYNX, VELA
- (4) Diginet: MMDM/RT, MEDM

222.0m	28. 2mm
	Transformed States Stat

PART NO.	LUMENS		WATT	CRI	DIMENSIONS	CUTOUT	WEIGHT	вох	CARTON	
	3000K	4000K	5700K	WATT	CRI	DIMENSIONS	01001	WEIGHT	вол	QTY
SHOPTRI	2900lm	3200lm	3000lm	35W	≥80	242x150x90mm	230x130mm	1.95kg	27x16x11cm	1/6

-**--**(}