



SURFACETRI

LED Dimmable Surface Mounted Oyster Lights


TRI-CCT

3000K


4000K

5000K

- Input voltage range: 220-240V
- Inbuilt constant current driver included
- Housing & faceplate: PC
- Diffuser: white PS
- Mounting bracket: aluminium
- Tri-CCT (3000K/ 4000K/ 5000K) in one fitting
- CCT switch on DC cable
- LED chips: SMD2835
- Power factor: 0.9
- CRI: ≥80
- Flex & plug not included
- Ambient temperature: -20 to 40°C
- Suitable for dimming
- Suitable for 2-way switching
- Suitable for use with motion or Microwave sensors




30,000hr
Lifetime




110°
Beam Angle


IP40
Rated




DIMMABLE




3 YEAR
Replacement
Warranty




SURFACETRI1R




SURFACETRI2R



SURFACETRI3R



SURFACETRI1S



SURFACETRI3S



Tested & Recommended Dimmers:

| BRAND | PART NO. | PCS PER DIMMER |
|---------|---|--|
| CLA | VELA | |
| CLIPSAL | 32E450UDM, 31E2PUDM, 32ELEDDM-WE, 32E450TM, PDL354PBDMUN-VW | SURFACETRI1R: 2-14PCS SURFACETRI2R: 2-8PCS SURFACETRI3R: 2-5PCS SURFACETRI1S: 2-14PCS SURFACETRI3S: 2-5PCS |
| HPM | Cat 250T, Cat 400T | |
| Diginet | MEDM, MMDM/RT | |

| PART NO. | DESCRIPTION | LUMENS (LM) | | | WATT (W) | CRI | BOX WEIGHT (kg) | BOX DIMENSIONS (cm) | CARTON QTY |
|---------------------|--------------------------------|-------------|-------|-------|----------|-----|-----------------|---------------------|------------|
| | | 3000K | 4000K | 5000K | | | | | |
| SURFACETRI1R | OYSTER DIMM LED S/M WH RND TRI | 420 | 480 | 450 | 6 | ≥80 | 0.25 | 13x45x13 | 1/40 |
| SURFACETRI2R | OYSTER DIMM LED S/M WH RND TRI | 840 | 960 | 900 | 12 | ≥80 | 0.4 | 19x45x19 | 1/40 |
| SURFACETRI3R | OYSTER DIMM LED S/M WH RND TRI | 1350 | 1550 | 1450 | 18 | ≥80 | 0.56 | 23.5x45x23.5 | 1/20 |
| SURFACETRI1S | OYSTER DIMM LED S/M WH SQ TRI | 420 | 480 | 450 | 6 | ≥80 | 0.27 | 13x45x13 | 1/40 |
| SURFACETRI3S | OYSTER DIMM LED S/M WH SQ TRI | 1350 | 1550 | 1450 | 18 | ≥80 | 0.66 | 23.5x45x23.5 | 1/20 |