



LED FILAMENT G95 & G125 DIMMABLE GLOBES




BC Base




ES Base

Product Features:

- Input voltage: 180-260V
- Heatsink: aluminium
- Diffuser: frosted glass
- LED chips: 4x24pcs 5131JC
- Power factor: >0.7
- CRI: >80
- Ambient temp: -20 to 50°C
- Suitable for use with dimmers
- Suitable for 2-way switching
- Suitable for use with sensors



G959-12 LINE DRAWING



G1259-12 LINE DRAWING

Tested & Recommended Dimmers:

Brand	Part No.
CLA	VELA
Legrand	Cat AR400A3PM
CLIPSAL	32ELEDM, 32E450TM, 31E2RUDM, 32E450UDM
DIGINET	MEDM

*Please check with Licenced electrician for Min and Max dimmer load

*May be compatible with other untested dimmers

Part No.	Description	Base	Kelvin	Lumens	Watt	CRI	Dimensions	Box Weight	Box Dimensions	Carton QTY
G95										
G959	GLOBE LED BC G95 6W FR DIMM	B22	2700K	600LM	6W	>80	Ø95x140mm	0.13kg	10x10x14cm	1/25/50
G9510	GLOBE LED ES G95 6W FR DIMM	E27	2700K	600LM	6W	>80	Ø95x140mm	0.13kg	10x10x14cm	1/25/50
G9511	GLOBE LED BC G95 6W FR DIMM	B22	6000K	600LM	6W	>80	Ø95x140mm	0.13kg	10x10x14cm	1/25/50
G9512	GLOBE LED ES G95 6W FR DIMM	E27	6000K	600LM	6W	>80	Ø95x140mm	0.13kg	10x10x14cm	1/25/50
G125										
G1259	GLOBE LED BC G125 8W FR DIMM	B22	2700K	800LM	8W	>80	Ø125x175mm	0.2kg	13x13x18cm	1/25/50
G12510	GLOBE LED ES G125 8W FR DIMM	E27	2700K	800LM	8W	>80	Ø125x175mm	0.2kg	13x13x18cm	1/25/50
G12511	GLOBE LED BC G125 8W FR DIMM	B22	6000K	800LM	8W	>80	Ø125x175mm	0.2kg	13x13x18cm	1/25/50
G12512	GLOBE LED ES G125 8W FR DIMM	E27	6000K	800LM	8W	>80	Ø125x175mm	0.2kg	13x13x18cm	1/25/50