



DIMMABLE GLS LED GLOBES (10W)

- Input voltage range: 176-264V AC 50/60Hz
- Constant current LED driver inbuilt
- Heat sink: aluminium-plastic
- Diffuser: plastic
- LED chips: SMD2835 LED
- Power factor: ≥ 0.7
- Ambient temp: -15 to 40°C
- Dimmable with most trailing edge and leading edge dimmers
- Suitable for 2-way switching
- Suitable for use with sensors



Tested & Recommended dimmers:

BRAND	CODE	Min/Max Globes per Dimmer
Clipsal	32E450UDM	1-8pcs
Clipsal	32E350UDM	1-6pcs
HPM Legrand	CAT400T	1-8pcs
CLA	LYNX	2-8pcs



PART NO.	DESCRIPTION	BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	DIMENSION (mm)	WEIGHT (kg)	BOX (cm)	CARTON QTY
GLS9DB	GLOBE LED BC GLS DIMM	B22	3000	810	10	>80	Ø60x108	0.15	11x11x6	10/50
GLS10DB	GLOBE LED ES GLS DIMM	E27	3000	810	10	>80	Ø60x109	0.10	11x7x7	10/50
GLS11DB	GLOBE LED BC GLS DIMM	B22	5000	850	10	>80	Ø60x108	0.10	11x11x6	10/50
GLS12DB	GLOBE LED ES GLS DIMM	E27	5000	850	10	>80	Ø60x109	0.15	11x11x6	10/50
GLS29D	GLOBE LED BC GLS DIMM	B22	4000	810	10	>80	Ø60x108	0.15	12x7x6.5	10/50
GLS30D	GLOBE LED ES GLS DIMM	E27	4000	810	10	>80	Ø60x108	0.15	12x7x6.5	10/50