





Globes - LED

## LED R7 GLOBES

- Input voltage range: 220-250V AC 50/60Hz
- Heat sink: aluminium
- LED chips: SMD2835 LED
- Power factor:  $\geq 0.5$
- Ambient temperature:  $-20$  to  $50^{\circ}\text{C}$
- Not suitable for dimming
- Suitable for 2 way switching
- Suitable for use with PIR sensors

25,000hr Lifetime	330° Beam Angle	<b>IP42</b> Rated	<b>3YEAR</b> Replacement Warranty
----------------------	--------------------	----------------------	---



CODE	DESCRIPTION	BASE	KELVIN	LUMENS	WATT	CRI	WEIGHT	BOX	CTN QTY
R71A	GLOBE LED R7 118MM 8W 3000K	R7	3000K	780LM	8=50	80	0.05kg	13x3x3cm	1/100
R72A	GLOBE LED R7 118mm 8W 5000K	R7	5000K	830LM	8=50	80	0.07kg	14x3x3cm	1/100
R73A	GLOBE LED R7 78mm 4W 3000K	R7	3000K	470LM	4=25	80	0.05kg	8x3x3cm	1/200
R74A	GLOBE LED R7 78mm 4W 5000K	R7	5000K	500LM	4=25	80	0.03kg	9x3x3cm	1/200